

FLATPOMP/10

SARGOMS

articoli gomma e plastica tecnico-industriali

Sargom s.r.l. via G. Bertoli, 15

25050 Rodengo Saiano (Bs)

Tel. 030/317741-6810320 - Fax 030/320882

Scheda tecnica (conforme a scheda produttore)

Distribuita da SARGOM S.R.L.



IMPIEGO

Tubo in gomma cord leggero ed appiattibile idoneo per scarico di acque sporche e industriali.

- **Temperatura:** -30°C +80°C

STRUTTURA

- **Sottostrato:** liscio in gomma nera SBR.
- **Rinforzi:** tessuti sintetici ad alta resistenza.
- **Copertura:** in gomma nera SBR/EPDM resistente all'abrasione e agli agenti atmosferici.
- **Superficie:** liscia ad impressione tela.
- **Marcatura:** listino scritta verde "H.T. - WATER DELIVERY - W.P. 10 BAR (150 PSI)"



APPLICATION

Softwall light and flat rubber hose suitable for discharge of industrial and waste water.

- **Temperature range:** -30°C +80°C

CONSTRUCTION

- **Tube:** black, smooth SBR rubber.
- **Reinforcement:** high strength synthetic textile plies.
- **Cover:** black, abrasion and weathering resistant SBR/EPDM rubber.
- **Surface:** smooth fabric finished.
- **Branding:** green transfer tape lettering "H.T. - WATER DELIVERY - W.P. 10 BAR (150 PSI)"

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS. ESERCIZIO WORKING PRESSURE		PRESS. SCOPPIO BURST PRESSURE		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mt	ft
30	1.3/16"	36	1.13/32"	0.36	0.24	10	150	30	450	40	131
32	1.1/4"	38	1.1/2"	0.41	0.28	10	150	30	450	40	131
35	1.3/8"	41	1.5/8"	0.45	0.30	10	150	30	450	40	131
38	1.1/2"	44	1.23/32"	0.48	0.32	10	150	30	450	40	131
40	1.9/16"	46	1.13/16"	0.50	0.34	10	150	30	450	40	131
45	1.3/4"	51	2"	0.56	0.38	10	150	30	450	40	131
51	2"	57	2.1/4"	0.74	0.50	10	150	30	450	40	131
60	2.3/8"	67	2.41/64"	0.84	0.56	10	150	30	450	40	131
70	2.3/4"	77	3.1/32"	0.97	0.65	10	150	30	450	40	131
76	3"	82	3.7/32"	1.03	0.69	10	150	30	450	40	131
80	3.5/32"	87	3.7/16"	1.10	0.74	10	150	30	450	40	131
90	3.17/32"	98	3.27/32"	1.45	0.97	10	150	30	450	40	131
102	4"	108	4.1/4"	1.57	1.06	10	150	30	450	40	131
120	4.3/4"	128	5.1/32"	1.93	1.30	10	150	30	450	40	131
152	6"	160	6.5/16"	2.70	1.81	10	150	30	450	40	131
203	8"	213	8.12/32"	4.70	3.15	10	150	30	450	20	65.5
254	10"	264	10.3/8"	6.10	4.09	10	150	30	450	20	65.5

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.
Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.

Rev. 1