

RIDUZIONE

estremità maschio filettata (1° R di riferimento) estremità femmina filettata (R₁ ridotto)




Fig. A




Fig. B

REDUCER

male parallel threaded (1st R of reference) socket parallel threaded (R₁ reduced)

REDUCTION DOUBLE

mâle fileté sur le 1^{er} R de référence, femelle taraudée sur le R₁ réduit

REDUZIERSTÜCK

mit zyl. Gewindestutzen/Gewindemuffe Anschluß nur für Kunststoffgewinde 21.091.18

	R x R ₁	PN	H	L ₁	L	E	K	Fig	g
R	1/2" x 3/8"	16	35	11,4	15	28	23	A	10
R	3/4" x 3/8"	16	36	11,4	16,3	34	28	A	12
R	3/4" x 1/2"	16	39	15	16,3	34	28	A	15
R	1" x 3/8"	16	41	11,4	19,1	40	35	A	20
R	1" x 1/2"	16	44	15	19,1	40	35	A	24
R	1" x 3/4"	16	46	16,3	19,1	40	35	A	25
R	1 1/4" x 1/2"	16	48	15	21,4	52	44	A	37
R	1 1/4" x 3/4"	16	49	16,3	21,4	52	44	A	37
R	1 1/4" x 1"	16	52	19,1	21,4	52	44	A	40
R	1 1/2" x 1/2"	16	52	15	21,4	58	51	A	46
R	1 1/2" x 3/4"	16	50	16,3	21,4	58	51	A	47
R	1 1/2" x 1"	16	55	19,1	21,4	58	51	A	52
R	1 1/2" x 1 1/4"	16	57	21,4	21,4	58	51	A	54
R	2" x 3/4"	16	60	16,3	25,7	70	64	A	80
R	2" x 1"	16	63	19,1	25,7	70	64	A	80
R	2" x 1 1/4"	16	65	21,4	25,7	70	64	A	85
R	2" x 1 1/2"	16	65	21,4	25,7	70	64	A	102
R	2 1/2" x 2"	16	56	25,7	30,2	-	80	B	155
R	3" x 2"	16	66	25,7	33,3	-	93	B	185
R	3" x 2 1/2"	16	66	30,2	33,3	-	93	B	200
R	4" x 3"	16	79	33,3	39,3	-	118	B	500

R: R/NA